



1385 *Serial Matrix Printer*

Key Features

- On board ethernet models available
- Ethernet hardware/software located on main logic board
- Ribbon motion detection (detects ribbon jams)
- PCL emulation model available
- Automatic paper width detection
- Up to 9-part forms
- LAN IPDS version available

Top speeds of 1100 CPS

At top speeds of 1100 CPS the 1385 keeps pace with the bustling, demanding world where printing is time sensitive and critical. Engineered for printing under adverse conditions, these devices produce multi-part invoices, shipping documents or bar code labels at a rate of 50,000 pages per month.

Affordable Upgrades

Optionally configured with three input tractors (two front, one rear), the 1385 is priced 50% lower than the competition. A straight paper path on the front tractors of the 1385 results in jam-free operation and flawless 24-wire impressions on up to 7-part forms. The 1385 offers fully automated gap adjustment, paper parking, loading, etc.

Ideal For Many Markets & Applications

Federal, State & Local Government- Print tax forms, payroll checks, expense reports, inventory reports, invoices. Manufacturing, Transportation, & Distribution - Print pick lists, shipping labels and freight bills. Excellent readability on all industry standard bar codes, including POSTNET.



SPECIFICATIONS

Print Speed (CPS)	At 10, 12, 15 cpi: Draft 800, 880, 1100; NLQ 245, 295, 370; LQ 120, 145, 185
Print Method	Serial Impact
Resolution	360 x 360 dpi
Throughput	626 pages per hour (ECMA 132)
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (Emulation dependent)
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 M Characters (draft)
Standard Connectivity	Bi-directional Centronics Parallel, Ethernet
Optional Connectivity	RS-232 Serial, Coax (SCS/IPDS), Twinax
Standard Emulation	IBM® Proprinter XL24e, Epson® LQ-2550, Epson® LQ-2170 (ESC P/2), MTPL
Optional Emulation	LA75
Fonts	Draft, Copy Draft, Courier, Roman, Sans Serif, OCR A, OCR B, 15 Bar Codes & scaleable LCP fonts
Consumables	20 M Character Ribbon
STD Paper Handling	Front insertion, Push tractor with paper parking and AGA
Number of Copies	Front: Original + 6 (7-part forms); Back: Original + 4 (5-part forms)
Paper Type	Continuous paper
Paper Size	Length: 4" min, 14" max; Width: 4" min, 14.5" max
Physical Weight	42 lbs
Physical Size	24.5" x 10.9" x 16.9"
Power Voltage	AC 230V and 120V (selectable)
Power Frequency	50/60H
Power Consumption	70 Watts
Compliance	Energy Star compliant, Ozone-free, RoHS
Workload	Up to 50,000 pages per month
Reliability MTBF	10,000 hours @ 100% duty cycle
Drivers	Windows XP, Server 2003, 2000, 95/98/ME, NT 4.0, SAP
Temperature	+10°C to +35°C
Humidity	5% to 85% (relative humidity)
Acoustic	53 dB (ISO 7779)
Warranty	1 year on-site
Optional Paper Handling	Second front push tractor, paper cutter, dual bin sheet feeder
Optional Accessories	Printer stand, paper basket, pedestal cabinet, cable cover, castors